

@dose

Electronic Metering Pump



- Provides constant dosing rate, even under voltage extremes
- Tried, tested & proven in installations across India
- Nationwide dealer network for prompt sales & service support

Designed & engineered for optimum performance

Technical Specifications

Dosing rate @ 4 kg/ cm ²	1.5, 3.0, 6.0 & 10.0 lph
Suction/ Discharge tubing	4/ 6 mm
Frequency	Up to 400 spm
Electrical	230 V AC, 50 Hz
Power consumption at 400 spm	30 Watts

Features

- Auto resetting fuse
- Double ball NRV with PTFE seals
- Splash proof enclosure
- Built in air release valve
- PTFE diaphragm for longer life
- Adjustable frequency (upto 400 spm)
- Compact and lightweight

Scope Of Supply

- e-dose pump
- Suction and discharge tubing
- Suction filter with NRV
- Anti siphon valve
- Mounting bolts
- O&M manual

Optional Advanced Features

- Level switch interlock
- External fault relay output
- 4 to 20 mA input
- Pulse input facility

In-house Manufacturing And Testing Facilities



- Solenoid coil winding, manufacturing and high voltage testing done in house ensuring optimum performance
- Every pump tested rigorously under simulated conditions

Color Options



Mounting Options



Wall Mounted



Tank Mounted

Your nearest authorised dealer :



Initiative Engineering

Sr. No. 273, Near Vitthal Mandir, Bhatewara Nagar
Hinjewadi, Pune 411 057, Maharashtra (India)

Tel.: (020) 2293 2122, 2293 2123

e-mail: edosepump@gmail.com